

Specification of Thermoelectric Module

TES1-12760L1-T200-SS-TF22-AIO

Description

The 127 couples, 29.7 mm x 29.7 mm size module is a single stage module which is made of our high performance ingot to achieve superior cooling performance and 70 °C or larger delta Tmax, is designed for superior cooling and heating applications. It is designed for superior cooling and heating up to 200 °C applications. Beyond the standard below, we can design and manufacture the custom made module according to your special requirements.

Features

- No moving parts, no noise, and solid-state
- Compact structure, small in size, light in weight
- Environmental friendly
- RoHS compliant
- Precise temperature control
- Exceptionally reliable in quality, high performance


Application

- Food and beverage service refrigerator
- Portable cooler box for cars
- Liquid cooling
- Temperature stabilizer
- CPU cooler and scientific instrument
- Photonic and medical systems

Performance Specification Sheet

Th (°C)	27	50	Hot side temperature at environment: dry air, N ₂
DT _{max} (°C)	70	79	Temperature Difference between cold and hot side of the module when cooling capacity is zero at cold side
U _{max} (Voltage)	15.8	17.1	Voltage applied to the module at DT _{max}
I _{max} (Amps)	6.0	6.0	DC current through the modules at DT _{max}
Q _{Cmax} (Watts)	60.8	65.5	Cooling capacity at cold side of the module under DT=0 °C
AC resistance (Ohms)	1.93	2.08	The module resistance is tested under AC
Tolerance (%)	± 10		For thermal and electricity parameters

Geometric Characteristics Dimensions in millimeters



Manufacturing Options

A. Solder:

1. T100: BiSn (Tmelt=138°C)
2. T200: CuAgSn (Tmelt = 217°C)
3. T240: SbSn (Tmelt = 240°C)

B. Sealant:

1. NS: No sealing (Standard)
2. SS: Silicone sealant
3. EPS: Epoxy sealant

C. Ceramics:

1. Alumina (Al₂O₃, white 96%)
2. Aluminum Nitride (AlN)

D. Ceramics Surface Options:

1. Blank ceramics (not metalized)
2. Metalized


Ordering Option

Suffix	Thickness (mm)	Flatness/ Parallelism (mm)	Lead wire length(mm) Standard/Optional length
TF	0:3.61±0.10	0:0.07/0.07	150±3/Specify

Specification of Thermoelectric Module



TES1-12760L1-T200-SS-TF22-AIO

Performance Curves at $T_h=27^\circ\text{C}$





Standard Performance Graph $Q_c = f(DT)$


Performance Curves at $T_h=50^\circ\text{C}$



Standard Performance Graph $V = f(DT)$




Standard Performance Graph $Q_c = f(V)$




Specification of Thermoelectric Module

TES1-12760L1-T200-SS-TF22-AIO



Performance Curves at Th=27 °C



Performance Curves at Th=50 °C



Standard Performance Graph COP = f(V) of DT ranged from 0 to 30 °C



Standard Performance Graph COP = f(V) of DT ranged from 40 to 60/70 °C

Remark: The coefficient of performance (COP) is the cooling power Q_c /Input power ($V \times I$).

Operation Caution

- Attach the cold side of module to the object to be cooled
- Attach the hot side of module to a heat radiator for heat dissipating
- Operation below I_{max} or V_{max}
- Work under DC

Note: All specifications subject to change without notice.